







Hi-Capacity

CONDENSATE REMOVAL PUMP

This high efficiency boiler pump offers unsurpassed performance and is ideal for commercial boiler applications.





550L/h max. flow



5m max. rec. head (flow rate 10L/h)


KEY FEATURES


- Easy access tank
- Twist & click non return outlet barb
- Built-in spirit level
- Plug & play

SUITABILITY

- Up to 200kW / 682,000Btu/h with condensate PH value >2.2
- ✓ Perfect for... Larger domestic commercial gas & oil fired condensing boilers








Non-return valve can be from 6mm to 10mm (see graphs below)	e cut
	The state of the s

HI-CAPACITY OPTIONS

Hi-Capacity (EU)

FP3356

HI-CAPACITY @ 230 VAC 50Hz			
Max. flow	550L/h @ 0 head		
Max. rec. head	5m		
Tank capacity	1.7L		
dB(A) @ 1m	44		
Power supply	230 VAC, 0.8A, 50Hz		
Rated	Non continuous		
Class	I appliance		
Max. unit output	200kW / 682,000 Btu/h		
Max. water temp	60°C / 140°F		
Inlet/outlet	x4 21-27mm in, 6-10mm out		
IP Protection	IP24		
Safety switch	3.0A Normally closed		
Thermal protection	✓		
Fully potted	n/a		
Self priming	n/a		



		LITILIA FER HOOK					
		6mm flov	N				
	6						
	5	1.		5m	max. reco	ommend	ed head
1EAD	4		·				
METRES HEAD	3		٠.,	·			
ME	2			٠.,	٠		
	1	230 VA	C			****	٠
	0	50	100		200 R HOUR	250	300

SUGGESTED XTRA ACCESSORIES

ı	JOGGESTED KINGT MCCESSONIES				
ĺ	Description		Part No.		
	Tube To Soil Stack Adaptor		FP2038		
	1 Amp Fuse		FP2620		
	Vinyl Tube Braided 1/4" (6mm)		AX5100		
	Vinyl Tube Braided		AX5101		



3/8" (10mm)

For more installation accessories take a look at our Aspen Xtra range

IN THE BOX

Hi-Capacity boiler pump • 2m Plug & play power cable • 6m discharge tube (10mm ID) • Pipe adaptor • Fixing kit • x4 feet • Install

Download manual at aspenpumps.com





Information correct at time of going to press



