

## Toshiba Air Conditioning - VRF Data Sheet

### MMY-MAP1006FT8P

### Three-pipe SHRMe - Super Heat Recovery Condensing Unit





#### Features

- Dual setpoint for more precision
- ESEER increased to > 8
- UK-SEER achievable to >10
- New 4 series flow box with 50 m run
- New 4- and 6-port multi-flow boxes

#### Technical Data

Model reference		MMY-MAP1006FT8P
Nominal cooling	kW	28.0
Nominal heating	kW	31.5
Capacity code		10
Min./max. capacities connectable	kW	22.4/37.8
Power input (cool/heat)	kW	7.96/7.05
SEER/ESEER Value (Office Profile)		7.55/8.03
SCOP/ESCOP Value (Office Profile)		5.12/5.35
Starting current	A	1
Running current (cool/heat)	A	12.49/11.06
Suggested fuse size	A	20
Power supply	V-ph-Hz	380/415-3-50
Interconnecting cable		2-core screened 1.5 mm
Sound power (cool/heat)	dB(A)	80/82
Sound pressure (cool/heat)	dB(A)	59/61
Standard air flow	m <sup>3</sup> /h	9700
Standard air flow	l/s	2694
External static pressure	Pa	50
Maximum indoor units connectable		22
Dimensions (H x W x D)	mm	1830 x 990 x 780
Unit weight	kg	263
R410A refrigerant base charge	kg	11

#### Dimensional Drawings



Cool Designs Ltd

Raising the Standards in Air Conditioning Distribution

[www.cdlweb.info](http://www.cdlweb.info)

