

## Toshiba Air Conditioning - VRF Data Sheet

### MMD-AP0274SPH-E Slim ducted

#### Features


- External static pressure can be raised up to 42 Pa
- Low noise: low fan speed down to 33 dB(A)
- Fresh air intake
- Lift pump up to 550 mm lift
- Ideal for restricted ceiling voids only 210 mm high
- Base or rear return air



#### Technical Data

Model reference		MMD-AP0274SPH-E
Nominal cooling	kW	8.0
Nominal heating	kW	9.0
Capacity code		3.0
Power input (cool/heat)	kW	0.105
UK cooling	kW	7.69
UK sensible cooling	kW	5.77
UK heating	kW	7.29
Starting current	A	1.13
Running current	A	0.75
Suggested fuse size	A	5
Power supply	V-ph-Hz	220/240-1-50
Interconnecting cable		2-core screened 1.5 mm
Sound power H-M-L (base/rear air inlet)	dB(A)	58-54-53/52-48-44
Sound pressure H-L (base/rear air inlet)	dB(A)	49-44/38-33
Standard air flow H-L	m <sup>3</sup> /h	1080-900
Standard air flow H-L	l/s	300-250
External static pressure (factory default)	Pa	2
Static pressure range	Pa	2-42 (4 steps)
Dimensions (H x W x D)	mm	210 x 1140 x 645
Unit weight	kg	29

#### Dimensional Drawings



Cool Designs Ltd

Raising the Standards in Air Conditioning Distribution

www.cdlweb.info

