TOSHIBA Leading Innovation >>>

Toshiba Air Conditioning - VRF Data Sheet

MMF-AP0366H-E Floor-mounted cabinet


Features

- Wide automatic vertical and horizontal air distribution with an angle up to 150°
- Large capacity range: cooling capacities from 4.5 kW to 16 kW, heating capacities from 5 kW to 18 kW
- Very small footprint 0.128 m² up to 8 kW and 0.243 m² up to 16 kW
- High air flows from 660 m³/h to 2160 m³/h

Technical Data

Model reference		MMF-AP0366H-E
Nominal cooling	kW	11.2
Nominal heating	kW	12.5
Capacity code		4.0
Power input (cool/heat)	kW	0.135
UK cooling	kW	10.2
UK sensible cooling	kW	7.8
UK heating	kW	10.05
Starting current	А	1.26
Running current	Α	0.90
Suggested fuse size	Α	5
Power supply	V-ph-Hz	220/240-1-50
Interconnecting cable		2-core screened 1.5 mm
Sound power H-M-L	dB(A)	64-61-55
Sound pressure H-L	dB(A)	51-41
Air flow H-L	m³/h	1920-1380
Air flow H-L	l/s	532-383
Dimensions (H x W x D)	mm	1750 x 600 x 390
Unit weight	kg	62

Dimensional Drawings





All UK duties are based on Cooling Indoor air temperature 22°C DB/16°C WB Outdoor air temperature 28°C DB 50% RH, high fan speed, 5 m pipe run. Heating Indoor air temperature 21°C DB Outdoor air temperature -4°C DB 100% RH, high fan speed, 5 m pipe run. Values are based on the maximum compressor output. Data obtained from Toshiba Air Conditioning Web Data July 2013.