TOSHIBA Leading Innovation >>>

Toshiba Air Conditioning - VRF Data Sheet

MMU-AP0154SH-E

1-way cassette


Features


- Compact size (200 x 1000 x 710 mm 4.5 to 7.1 kW)
- Low noise down to 32 dB(A) (4.5 kW)
- Fresh air intake
- Lift pump up to 350 mm lift
- Ideal for restricted ceiling voids


Technical Data

Model reference		MMU-AP0154SH-E
Nominal cooling	kW	4.5
Nominal heating	kW	5.0
Capacity code		1.7
Power input (cool/heat)	kW	0.042
UK cooling	kW	4.33
UK sensible cooling	kW	3.24
UK heating	kW	4.05
Starting current	A	0.51
Running current	A	0.34
Suggested fuse size	A	5
Power supply	V-ph-Hz	220/240-1-50
Interconnecting cable		2-core screened 1.5 mm
Sound power H-M-L	dB(A)	52-50-47
Sound pressure H-L	dB(A)	37-32
Air flow H-L	m³/h	750-630
Air flow H-L	l/s	208-175
Dimensions (H x W x D)	mm	200 x 1000 x 710
Unit weight	kg	21
Panel reference		RBC-US21GE
Panel dimensions $(H \times W \times D)$	mm	20 x 1230 x 800

Dimensional Drawings







Cool Designs Ltd

Raising the Standards in Air Conditioning Distribution

www.cdlweb.info



All UK duties are based on Cooling Indoor air temperature 22°C DB/16°C WB Outdoor air temperature 28°C DB 50% RH, high fan speed, 5 m pipe run. Heating Indoor air temperature 21°C DB Outdoor air temperature -4°C DB 100% RH, high fan speed, 5 m pipe run. Values are based on the maximum compressor output. Data obtained from Toshiba Air Conditioning Web Data July 2013.

