TOSHIBA Leading Innovation >>>

Toshiba Air Conditioning - VRF Data Sheet

MMU-AP0184HP-E 4-way cassette

Features


- Individual louvre control
- Self-cleaning operation
- Auxiliary fresh air intake
- Lift pump up to 850 mm lift
- Removable corner "Pockets" for easy installation
- Long life pre-filter

Technical Data



Model reference		MMU-AP0184HP-E
Nominal cooling	kW	5.6
Nominal heating	kW	6.3
Capacity code		2.0
Power input (cool/heat)	kW	0.026
UK cooling	kW	5.28
UK sensible cooling	kW	4.04
UK heating	kW	5.1
Starting current	A	0.36
Running current	A	0.29
Suggested fuse size	A	5
Power supply	V-ph-Hz	220/240-1-50
Interconnecting cable		2-core screened 1.5 mm
Sound power H-M-L	dB(A)	47-44-42
Sound pressure H-L	dB(A)	32-27
Air flow H-L	m³/h	1050-800
Air flow H-L	l/s	292-222
Dimensions (H x W x D)	mm	256 x 840 x 840
Unit weight	kg	20
Panel reference		RBC-U31PG(W)-E
Panel dimensions $(H \times W \times D)$	mm	30 x 950 x 950


Dimensional Drawings





Raising the Standards in Air Conditioning Distribution

www.cdlweb.info





All UK duties are based on Cooling Indoor air temperature 22°C DB/16°C WB Outdoor air temperature 28°C DB 50% RH, high fan speed, 5 m pipe run. Heating Indoor air temperature 21°C DB Outdoor air temperature -4°C DB 100% RH, high fan speed, 5 m pipe run. Values are based on the maximum compressor output. Data obtained from Toshiba Air Conditioning Web Data July 2013.