

Toshiba Air Conditioning - RAV-SM Data Sheet

RAV-SM2246AT8-E Outdoor Unit

Features


- R22 and R407C replacement technology
- Wide operating range (cooling mode -15°C to +52°C)
- Extended pipe runs up to 100 m (1104/1404)
- Flexible, can be utilised for single, twin, triple indoor applications
- Increased energy efficiency/cost saving



Technical Data

Model reference		RAV-SM2246AT8-E
Nominal cooling	kW	19.0
Nominal heating	kW	22.4
Maximum air flow	m ³ /h	9180
Maximum air flow	l/s	2550
Sound power (cool/heat)	dB(A)	76/76
Sound pressure (cool/heat)	dB(A)	58/60
Dimensions (H x W x D)	mm	1550 x 1010 x 370
Unit weight	kg	142
Power supply	V-ph-Hz	380/415-3-50
Interconnecting cable		3 core + earth
Suggested fuse size	A	16
Maximum operating current (cooling)	A	10.78
Operating range, cooling	°C	-15 to 52
Operating range, heating	°C	-27 to 15
Pipe sizes (liquid - suction)	inch	1/2 - 1-1/8
Minimum/maximum pipe length	m	5/100
Maximum height difference	m	30
Pre-charge pipe length	m	30

Dimensional Drawings



Cool Designs Ltd

Raising the Standards in Air Conditioning Distribution

www.cdlweb.info

