

Toshiba Air Conditioning - RAV-SM Data Sheet

RAV-SM804ATP-E Outdoor Unit

Features


- R22 and R407C replacement technology
- Wide operating range (cooling mode -15°C to +46°C)
- Auto-diagnostic function
- Flexible, can be utilised for single, twin, triple indoor applications
- Compact size



Technical Data

Model reference		RAV-SM804ATP-E
Nominal cooling	kW	6.7
Nominal heating	kW	8.0
Standard air flow	m ³ /h	2700
Standard air flow	l/s	750
Sound power (cool/heat)	dB(A)	65/69
Sound pressure (cool/heat)	dB(A)	48/52
Dimensions (H x W x D)	mm	550 x 780 x 290
Unit weight	kg	44
Power supply	V-ph-Hz	220/240-1-50/60
Interconnecting cable		3 core + earth
Suggested fuse size	A	16
Maximum operating current (cooling)	A	11.15
Operating range, cooling	°C	-15 to 46
Operating range, heating	°C	-15 to 15
Pipe sizes (liquid-suction)	inch	3/8-5/8
Minimum/maximum pipe length	m	5/30
Maximum height difference	m	30
Pre-charge pipe length	m	20
Additional R410A refrigerant - factory charge	g/m - kg	40 - 1.7

Dimensional Drawings



Cool Designs Ltd

Raising the Standards in Air Conditioning Distribution

www.cdlweb.info

