TOSHIBA Leading Innovation >>>

Toshiba Air Conditioning - Controls Data Sheet

RBC-AS41E Simplified Remote Controller

Features


- Compatible with all R410A Digital/Super Digital Inverter and VRF systems*
- Reduced function display provides easy-to-read/understand layout
- Built-in room temperature sensor
- 2 controllers can be used on the same indoor/group
- Individual or group control of up to 8 units under simultaneous control
- Test-run function available
- 0.5 degree set point change
- * Not compatible with DI Flexi.
- ** Feature available on specific models and unit combinations.



Technical Data

| Model reference | | RBC-AS41E |
|-------------------------------------|---------------------------------|-----------------|
| Total dimensions (H x W x D) | mm | 120 x 70 x 18 |
| Electrical connection (low voltage) | | Screw terminals |
| | | |
| Functions | Setting | Monitor |
| On/Off | ✓ | ✓ |
| Mode | Auto, Heat, Cool, Dry, Fan Only | ✓ |
| Set point | 18-29°C | ✓ |
| Fan speed | Auto, High, Medium, Low | ✓ |
| Louvre | Swing, Fix | ✓ |
| Filter display | Х | Х |
| Fault code | Reset | Hexadecimal |
| Countdown timer | Х | Х |
| Schedule timer | X | Х |

Dimensional Drawings



Cool Designs Ltd

Raising the Standards in Air Conditioning Distribution

www.cdlweb.info



