



## Toshiba Air Conditioning Data Sheet

RAV-GM1601AT8P-E  
Digital Inverter 6 HP 3 Phase

Model Reference		RAV-GM1601AT8P-E	
Operating Range	Cooling/Heating	°C	-15 to 46/-15 to 15
Air Flow	High	m <sup>3</sup> /h - l/s	6900 - 1917
Sound	Pressure High Cooling/Heating	dB(A)	53 - 55
	Power High Cooling/Heating	dB(A)	70 - 72
Unit	Height x Width x Depth	mm	1340 x 900 x 320
	Weight	kg	94
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8
	Min.-Max. Length	m	5 - 50
	Maximum Height Difference	m	±30
	Drain Port Connection	mm	16
Refrigerant R32	Gas - Base Charge/Chargeless Length	kg/m	R32 - 2.4/30
	Additional Charge Liquid Side	g/m	35
Run Current	Maximum	Amps	7.23
Power Cable	Outdoor to Indoor		3 core + earth
Power Supply	Suggested Fuse Size	V/ph/Hz-A	380-415/3/50

\* Waiting for published data

# TOSHIBA

- Redesigned for use with refrigerant R32
- Wide operating range (cooling mode -15°C to +52°C)
- Auto-diagnostic function
- Flexible, can be utilised for single, twin, triple indoor applications
- Compact size

## Outdoor Unit

	Name	Note
①	Refrigerant piping hole Indoor/Outdoor Unit connecting wire inlet hole	—
②	Power supply inlet hole	dia.38 Knockout hole

