



Toshiba Air Conditioning Data Sheet

RAV-GM901ATP-E
Digital Inverter 6 HP 1 Phase

Model Reference		RAV-GM901ATP-E	
Operating Range	Cooling/Heating	°C	-15 to 46/-15 to 15
Air Flow	High	m ³ /h - l/s	2,900
Sound	Pressure High Cooling/Heating	dB(A)	51 - 68
	Power High Cooling/Heating	dB(A)	68 - 72
Unit	Height x Width x Depth	mm	630 x 800 x 300
	Weight	kg	47
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8
	Min.-Max. Length	m	5 - 50
	Maximum Height Difference	m	±30
	Drain Port Connection	mm	16
Refrigerant R32	Gas - Base Charge/Chargeless Length	kg/m	R32 - 2.0/20
	Additional Charge Liquid Side	g/m	35
Run Current	Maximum	Amps	*-
Power Cable	Outdoor to Indoor		3 core + earth
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-16

* Waiting for published data

TOSHIBA

- Redesigned for use with refrigerant R32
- Wide operating range (cooling mode -15°C to +52°C)
- Auto-diagnostic function
- Flexible, can be utilised for single, twin, triple indoor applications
- Compact size

