

Toshiba Air Conditioning Data Sheet

RAV-RM1601CTP-E
Ceiling



Model Reference		RAV-RM1601CTP-E	
Nominal	Cooling Capacity	kW	14.0
	Heating Capacity	kW	16.0
	EER/COP	W/W	3.01/3.90
UK	Cooling Total / Sensible	kW	13.3/9.3
	Heating	kW	10.88
Cooling EN14825	Range Min-Max	kW	3.0 - 16.0
	Power Input	kW	4.65
	Pdesign	kW	12.0
	SEER/Energy Efficiency Class		5.90/233.0
	Seasonal Energy Consumption	kWh/a	831
Heating EN14825	Range Min-Max	kW	3.0 - 18.0
	Power Input	kW	4.69
	Pdesign	kW	8.0
	SCOP/Energy Efficiency Class		4.35/171.0
	Seasonal Energy Consumption	kWh/a	2732
Airflow	High - Medium - Low	l/s	567 - 425 - 333
	High - Medium - Low	m ³ /h	2040 - 1530 - 1200
Sound	Pressure: High - Medium - Low	dB(A)	46 - 41 - 35
	Power: High - Medium - Low	dB(A)	61 - 56 - 50
Dimensions	Height x Width x Depth	mm	235 x 1586 x 690
	Weight	kg	37
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8
	Drain Pipe Connection Upper - lower	mm	VP26/20
Remote Controller			Optional
Power Cable	Outdoor to Indoor		3 core + earth

* Waiting for published data

TOSHIBA

- Redesigned for use with refrigerant R32
- The best solution when no ceiling void is available
- Self-cleaning
- Air flow angle is automatically set to the most suitable setting, according to requirements

■ External dimensions

(Unit: mm)

