

Toshiba Air Conditioning Data Sheet

MMC-UP0151HP-E
VRF CEILING SUSPENDED



Model Reference		MMC-UP0151HP-E	
Capacity Code	Cooling Capacity	HP	1.7
Nominal	Heating Capacity	kW	4.5
	Cooling Total/Sensible	kW	5.0
UK	Heating	kW	4.1/3.0
	Power Input	kW	3.4
Electrical	Power Input	kW	0.033
	Run Current	Amps	0.38
	Start Current	Amps	0.54
Air Flow	High - Medium - Low	l/s	233 - 200 - 150
	High - Medium - Low	m ³ /h	840 - 690 - 540
Sound	Pressure High - Medium - Low	dB(A)	36 - 34 - 28
	Power High - Medium - Low	dB(A)	51 - 49 - 43
Unit	Height x Width x Depth	mm	235 x 950 x 690
	Weight	kg	24
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	26/20
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

TOSHIBA

- Optimum louver control
- High air flow distance up to 8m.
- Low noise levels
- Self-cleaning function
- Drain pump available

External dimensions

(Unit: mm)

