

Toshiba Air Conditioning Data Sheet

MMC-UP0181HP-E
VRF CEILING SUSPENDED



Model Reference		MMC-UP0181HP-E	
Capacity Code	Cooling Capacity	HP	2.0
Nominal	Heating Capacity	kW	5.6
	Cooling Total/Sensible	kW	6.3
UK	Heating	kW	5.1/3.7
	Power Input	kW	4.3
Electrical	Power Input	kW	0.034
	Run Current	Amps	0.39
	Start Current	Amps	0.55
Air Flow	High - Medium - Low	l/s	267 - 200 - 150
	High - Medium - Low	m ³ /h	960 - 720 - 540
Sound	Pressure High - Medium - Low	dB(A)	37 - 35 - 28
	Power High - Medium - Low	dB(A)	52 - 50 - 43
Unit	Height x Width x Depth	mm	235 x 950 x 690
	Weight	kg	24
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	26/20
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

TOSHIBA

- Optimum louver control
- High air flow distance up to 8m.
- Low noise levels
- Self-cleaning function
- Drain pump available

External dimensions

(Unit: mm)

