

Toshiba Air Conditioning Data Sheet

MMC-UP0361HP-E
VRF CEILING SUSPENDED



| Model Reference | MMC-UP0361HP-E | | |
|----------------------|----------------------------------|-------------------|--------------------|
| Capacity Code | Cooling Capacity | HP | 4.0 |
| Nominal | Heating Capacity | kW | 11.2 |
| | Cooling Total/Sensible | kW | 12.5 |
| UK | Heating | kW | 10.2/7.2 |
| | Power Input | kW | 8.5 |
| Electrical | Power Input | kW | 0.083 |
| | Run Current | Amps | 0.80 |
| | Start Current | Amps | 1.16 |
| Air Flow | High - Medium - Low | l/s | 517 - 383 - 283 |
| | High - Medium - Low | m ³ /h | 1860 - 1350 - 1020 |
| Sound | Pressure High - Medium - Low | dB(A) | 44 - 38 - 32 |
| | Power High - Medium - Low | dB(A) | 59 - 53 - 47 |
| Unit | Height x Width x Depth | mm | 235 x 1586 x 690 |
| | Weight | kg | 39 |
| Pipe Connection | Flare Connections (gas - liquid) | inch | 5/8 - 3/8 |
| | Drain Pipe Connection OD/ID | mm | 26/20 |
| Power Supply | Suggested Fuse Size | V/ph/Hz-A | 220-240/1/50-5 |

TOSHIBA

- Optimum louver control
- High air flow distance up to 8m.
- Low noise levels
- Self-cleaning function
- Drain pump available

External dimensions

(Unit: mm)

