

Toshiba Air Conditioning Data Sheet

MMC-UP0481HP-E
VRF CEILING SUSPENDED



Model Reference	MMC-UP0481HP-E		
Capacity Code	Cooling Capacity	HP	5.0
Nominal	Heating Capacity	kW	14
	Cooling Total/Sensible	kW	16
UK	Heating	kW	12.7/9.3
	Power Input	kW	10.9
Electrical	Power Input	kW	0.083
	Run Current	Amps	0.80
	Start Current	Amps	1.16
Air Flow	High - Medium - Low	l/s	517 - 433 - 333
	High - Medium - Low	m ³ /h	1860 - 1530 - 1200
Sound	Pressure High - Medium - Low	dB(A)	44 - 41 - 35
	Power High - Medium - Low	dB(A)	59 - 56 - 50
Unit	Height x Width x Depth	mm	235 x 1586 x 690
	Weight	kg	39
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	26/20
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

TOSHIBA

- Optimum louver control
- High air flow distance up to 8m.
- Low noise levels
- Self-cleaning function
- Drain pump available

External dimensions

(Unit: mm)

