

Toshiba Air Conditioning Data Sheet

MMU-UP0121MH-E
VRF 4 WAY COMPACT CASSETTE



Model Reference	MMU-UP0121MH-E		
Capacity Code	Cooling Capacity	HP	1.3
Nominal	Heating Capacity	kW	3.6
	Cooling Total/Sensible	kW	4.0
UK	Heating	kW	3.3/2.5
	Power Input	kW	2.2
Electrical	Power Input	kW	0.027
	Run Current	Amps	0.25
	Start Current	Amps	0.44
Air Flow	High - Medium - Low	l/s	165 - 140 - 112
	High - Medium - Low	m ³ /h	594 - 504 - 402
Sound	Pressure High - Medium - Low	dB(A)	38 - 34 - 30
	Power High - Medium - Low	dB(A)	53 - 49 - 45
Unit	Height x Width x Depth	mm	256 x 575 x 575
	Weight	kg	15
Panel	Height x Width x Depth	mm	12 x 620 x 620
	Weight RBC-U41PG(W)-E	kg	2.5
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4
	Drain Pipe Connection OD/ID	mm	VP20
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-3

TOSHIBA

- Smart flat-panel design
- Fit within the T-bar of grid ceiling; 620mm X 620mm
- User programmable 5-step flow
- Occupancy motion sensor
- Compact chassis perfectly suited to confined spaces.
- Built-in high lift drain pump.
- Lightweight unit, for easy and quick installation.

