

Toshiba Air Conditioning Data Sheet

MMD-UP0961HP-E
VRF HIGH STATIC DUCTED



Model Reference	MMD-UP0961HP-E		
Capacity Code	Cooling Capacity	HP	10.0
Nominal	Heating Capacity	kW	28.0
	Cooling Total/Sensible	kW	31.5
UK	Heating	kW	25.4/17.3
	Power Input	kW	21.4
Electrical	Power Input	kW	0.790
	Run Current	Amps	3.77
	Start Current	Amps	7.80
Air Flow	High - Medium - Low	l/s	1333 - 1167 - 972
	High - Medium - Low	m ³ /h	4800 - 4200 - 3500
External Static Pressure	Standard	Pa	150
	Maximum	Pa	250
Sound	Pressure High - Medium - Low	dB(A)	46 - 42 - 38
	Power High - Medium - Low	dB(A)	61 - 57 - 53
Unit	Height x Width x Depth	mm	448 x 1400 x 900
	Weight	kg	97
Pipe Connection	Flare Connections (gas - liquid)	inch	7/8 - 1/2
	Drain Pipe Connection OD/ID	mm	32/25
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-16

TOSHIBA

- Ultra-flexible, invisible and silent unit
- Diffuser design flexibility
- Unobtrusive, flexible and compact
- Static pressure can be set to 7 levels from 50 to 250Pa
- Long-life filter and air discharge spigot available
- Built-in high-lift drain pump (sizes 18 to 56)

External dimensions

(Unit: mm)

