

## Toshiba Air Conditioning Data Sheet

MMC-UP0241HP-E  
VRF CEILING SUSPENDED



Model Reference		MMC-UP0241HP-E	
<b>Capacity Code</b>		HP	2.5
Nominal	Cooling Capacity	kW	7.1
	Heating Capacity	kW	8
UK	Cooling Total/Sensible	kW	6.4/4.8
	Heating	kW	5.4
Electrical	Power Input	kW	0.067
	Run Current	Amps	0.68
	Start Current	Amps	0.97
Air Flow	High - Medium - Low	l/s	400 - 283 - 217
	High - Medium - Low	m <sup>3</sup> /h	1440 - 1020 - 750
Sound	Pressure High - Medium - Low	dB(A)	41 - 36 - 29
	Power High - Medium - Low	dB(A)	56 - 51 - 44
Unit	Height x Width x Depth	mm	235 x 1270 x 690
	Weight	kg	30
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	26/20
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

# TOSHIBA

- Optimum louver control
- High air flow distance up to 8m.
- Low noise levels
- Self-cleaning function
- Drain pump available

## External dimensions

(Unit: mm)

