

Toshiba Air Conditioning Data Sheet

MMC-UP0361HP-E
VRF CEILING SUSPENDED



Model Reference		MMC-UP0361HP-E	
Capacity Code		HP	4.0
Nominal	Cooling Capacity	kW	11.2
	Heating Capacity	kW	12.5
UK	Cooling Total/Sensible	kW	10.2/7.2
	Heating	kW	8.5
Electrical	Power Input	kW	0.083
	Run Current	Amps	0.80
	Start Current	Amps	1.16
Air Flow	High - Medium - Low	l/s	517 - 383 - 283
	High - Medium - Low	m ³ /h	1860 - 1350 - 1020
Sound	Pressure High - Medium - Low	dB(A)	44 - 38 - 32
	Power High - Medium - Low	dB(A)	59 - 53 - 47
Unit	Height x Width x Depth	mm	235 x 1586 x 690
	Weight	kg	39
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	26/20
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

TOSHIBA

- Optimum louver control
- High air flow distance up to 8m.
- Low noise levels
- Self-cleaning function
- Drain pump available

External dimensions

(Unit: mm)

