

Toshiba Air Conditioning Data Sheet

MMC-UP0561HP-E
VRF CEILING SUSPENDED



Model Reference		MMC-UP0561HP-E	
Capacity Code		HP	6.0
Nominal	Cooling Capacity	kW	16
	Heating Capacity	kW	18
UK	Cooling Total/Sensible	kW	14.5/9.4
	Heating	kW	12.2
Electrical	Power Input	kW	0.111
	Run Current	Amps	1.03
	Start Current	Amps	1.49
Air Flow	High - Medium - Low	l/s	567 - 467 - 350
	High - Medium - Low	m ³ /h	2040 - 1650 - 1260
Sound	Pressure High - Medium - Low	dB(A)	46 - 42 - 36
	Power High - Medium - Low	dB(A)	61 - 57 - 51
Unit	Height x Width x Depth	mm	235 x 1586 x 690
	Weight	kg	39
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	26/20
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

TOSHIBA

- Optimum louver control
- High air flow distance up to 8m.
- Low noise levels
- Self-cleaning function
- Drain pump available

External dimensions

(Unit: mm)

