


Toshiba Air Conditioning Data Sheet

MMU-UP0091H-E
VRF 4 WAY SMART CASSETTE



Model Reference		MMU-UP0091H-E	
Capacity Code		HP	1
Nominal	Cooling Capacity	kW	2.8
	Heating Capacity	kW	3.2
UK	Cooling Total/Sensible	kW	2.5/2.0
	Heating	kW	2.2
Electrical	Power Input	kW	0.020
	Run Current	Amps	0.20
	Start Current	Amps	0.30
Air Flow	High - Medium - Low	l/s	235 - 213 - 197
	High - Medium - Low	m3/h	846 - 768 - 708
Sound	Pressure High - Medium - Low	dB(A)	30 - 28 - 26
	Power High - Medium - Low	dB(A)	45 - 43 - 42
Unit	Height x Width x Depth	mm	256 x 840 x 840
	Weight	kg	18
Panel	Height x Width x Depth	mm	30 x 950 x 950
	Weight RBC-U41PG(W)-E	kg	5
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4
	Drain Pipe Connection OD/ID	mm	32/25
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

TOSHIBA

- Top class SEER and SCOP
- Energy saving with the occupancy sensor
- Unique louvre design for optimal air distribution
- Individual setting of louver position: 3 different swing modes: standard, diagonally, opposite or turn around
- 5 fan steps to precisely control the air flow.
- Simple & elegant design fits various rooms.

MMU-UP0091H-E, MMU-UP0121H-E

