

## Toshiba Air Conditioning Data Sheet

MMU-UP0091WH-E  
VRF 2 WAY CASSETTE



Model Reference		MMU-UP0091WH-E	
<b>Capacity Code</b>		HP	1.0
Nominal	Cooling Capacity	kW	2.8
	Heating Capacity	kW	3.2
UK	Cooling Total/Sensible	kW	2.5/1.9
	Heating	kW	2.2
Electrical	Power Input	kW	0.029
	Run Current	Amps	0.23
	Start Current	Amps	0.35
Air Flow	High - Medium - Low	l/s	155 - 138 - 125
	High - Medium - Low	m <sup>3</sup> /h	558 - 498 - 450
Sound	Pressure High - Medium - Low	dB(A)	34 - 32 - 30
	Power High - Medium - Low	dB(A)	49 - 47 - 45
Unit	Height x Width x Depth	mm	295 x 815 x 570
	Weight	kg	19
Panel	Height x Width x Depth	mm	20 x 1050 x 680
	Weight RBC-UW283PG(W)-E	kg	10
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4
	Drain Pipe Connection OD/ID	mm	32/25
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

# TOSHIBA

- Unique air flow control
- Enhanced indoor air quality with standard long-life filters
- Elegant white decoration panel
- Minimal weight (19 kg) for units up to 4.5kw
- Compact dimensions (height 295mm)
- Built-in drain pump

## UP007 to UP015

### ▼ Refrigerant pipe connecting port

Model: MMU-	Gas side: A
UP007 to UP012	9.5
UP015	12.7

