

Toshiba Air Conditioning Data Sheet

MMU-UP0151MH-E
VRF 4 WAY COMPACT CASSETTE



Model Reference		MMU-UP0151MH-E	
Capacity Code		HP	1.7
Nominal	Cooling Capacity	kW	4.5
	Heating Capacity	kW	5.0
UK	Cooling Total/Sensible	kW	4.1/3.1
	Heating	kW	2.7
Electrical	Power Input	kW	0.030
	Run Current	Amps	0.28
	Start Current	Amps	0.50
Air Flow	High - Medium - Low	l/s	183 - 153 - 130
	High - Medium - Low	m ³ /h	660 - 552 - 468
Sound	Pressure High - Medium - Low	dB(A)	40 - 35 - 31
	Power High - Medium - Low	dB(A)	55 - 50 - 46
Unit	Height x Width x Depth	mm	256 x 575 x 575
	Weight	kg	15
Panel	Height x Width x Depth	mm	12 x 620 x 620
	Weight RBC-U41PG(W)-E	kg	2.5
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	VP20
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-3

TOSHIBA

- Smart flat-panel design
- Fit within the T-bar of grid ceiling: 620mm X 620mm
- User programmable 5-step flow
- Occupancy motion sensor
- Compact chassis perfectly suited to confined spaces.
- Built-in high lift drain pump.
- Lightweight unit, for easy and quick installation.

