

Toshiba Air Conditioning Data Sheet

MMU-UP0151WH-E
VRF 2 WAY CASSETTE



Model Reference		MMU-UP0151WH-E	
Capacity Code		HP	1.7
Nominal	Cooling Capacity	kW	4.5
	Heating Capacity	kW	5.0
UK	Cooling Total/Sensible	kW	4.1/2.9
	Heating	kW	3.4
Electrical	Power Input	kW	0.030
	Run Current	Amps	0.24
	Start Current	Amps	0.36
Air Flow	High - Medium - Low	l/s	167 - 148 - 125
	High - Medium - Low	m ³ /h	600 - 534 - 450
Sound	Pressure High - Medium - Low	dB(A)	35 - 33 - 30
	Power High - Medium - Low	dB(A)	50 - 48 - 45
Unit	Height x Width x Depth	mm	295 x 815 x 570
	Weight	kg	19
Panel	Height x Width x Depth	mm	20 x 1050 x 680
	Weight RBC-UW283PG(W)-E	kg	10
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	32/25
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

TOSHIBA

- Unique air flow control
- Enhanced indoor air quality with standard long-life filters
- Elegant white decoration panel
- Minimal weight (19 kg) for units up to 4.5kw
- Compact dimensions (height 295mm)
- Built-in drain pump

UP007 to UP015

▼ Refrigerant pipe connecting port

Model: MMU-	Gas side: A
UP007 to UP012	9.5
UP015	12.7

