


Toshiba Air Conditioning Data Sheet

MMU-UP0181H-E
VRF 4 WAY SMART CASSETTE



Model Reference		MMU-UP0181H-E	
Capacity Code		HP	2
Nominal	Cooling Capacity	kW	5.6
	Heating Capacity	kW	6.3
UK	Cooling Total/Sensible	kW	5.1/3.8
	Heating	kW	4.3
Electrical	Power Input	kW	0.026
	Run Current	Amps	0.26
	Start Current	Amps	0.39
Air Flow	High - Medium - Low	l/s	350 - 306 - 261
	High - Medium - Low	m ³ /h	1260 - 1100 - 940
Sound	Pressure High - Medium - Low	dB(A)	36 - 33 - 31
	Power High - Medium - Low	dB(A)	50 - 47 - 45
Unit	Height x Width x Depth	mm	319 x 840 x 840
	Weight	kg	25
Panel	Height x Width x Depth	mm	30 x 950 x 950
	Weight RBC-U41PG(W)-E	kg	5
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	32/25
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

TOSHIBA

- Top class SEER and SCOP
- Energy saving with the occupancy sensor
- Unique louvre design for optimal air distribution
- Individual setting of louver position: 3 different swing modes: standard, diagonally, opposite or turn around
- 5 fan steps to precisely control the air flow.
- Simple & elegant design fits various rooms.

MMU-UP0151H-E, MMU-UP0181H-E

