

Toshiba Air Conditioning Data Sheet

MMU-UP0181WH-E
VRF 2 WAY CASSETTE



Model Reference		MMU-UP0181WH-E	
Capacity Code		HP	2.0
Nominal	Cooling Capacity	kW	5.6
	Heating Capacity	kW	6.3
UK	Cooling Total/Sensible	kW	5.1/3.7
	Heating	kW	4.3
Electrical	Power Input	kW	0.044
	Run Current	Amps	0.32
	Start Current	Amps	0.48
Air Flow	High - Medium - Low	l/s	250 - 208 - 172
	High - Medium - Low	m ³ /h	900 - 750 - 618
Sound	Pressure High - Medium - Low	dB(A)	35 - 33 - 30
	Power High - Medium - Low	dB(A)	50 - 48 - 45
Unit	Height x Width x Depth	mm	345 x 1180 x 570
	Weight	kg	26
Panel	Height x Width x Depth	mm	20 x 1415 x 680
	Weight RBC-UW803PG(W)-E	kg	14
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	32/25
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

TOSHIBA

- Unique air flow control
- Enhanced indoor air quality with standard long-life filters
- Elegant white decoration panel
- Minimal weight (19 kg) for units up to 4.5kw
- Compact dimensions (height 295mm)
- Built-in drain pump

UP018 to UP030

(Unit: mm)

▼ Refrigerant pipe connecting port

Model: MMU-	Liquid side: A	Gas side: B
UP018	6.4	12.7
UP024 to UP030	9.5	15.9

