

Toshiba Air Conditioning Data Sheet

MMU-UP0271WH-E
VRF 2 WAY CASSETTE



Model Reference		MMU-UP0271WH-E	
Capacity Code		HP	3.0
Nominal	Cooling Capacity	kW	8.0
	Heating Capacity	kW	9.0
UK	Cooling Total/Sensible	kW	7.3/5.0
	Heating	kW	6.1
Electrical	Power Input	kW	0.054
	Run Current	Amps	0.39
	Start Current	Amps	0.59
Air Flow	High - Medium - Low	l/s	292 - 233 - 205
	High - Medium - Low	m ³ /h	1050 - 840 - 738
Sound	Pressure High - Medium - Low	dB(A)	38 - 35 - 33
	Power High - Medium - Low	dB(A)	53 - 50 - 48
Unit	Height x Width x Depth	mm	345 x 1180 x 570
	Weight	kg	26
Panel	Height x Width x Depth	mm	20 x 1415 x 680
	Weight RBC-UW803PG(W)-E	kg	14
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	32/25
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

TOSHIBA

- Unique air flow control
- Enhanced indoor air quality with standard long-life filters
- Elegant white decoration panel
- Minimal weight (19 kg) for units up to 4.5kw
- Compact dimensions (height 295mm)
- Built-in drain pump

UP018 to UP030

(Unit: mm)

▼ Refrigerant pipe connecting port

Model: MMU-	Liquid side: A	Gas side: B
UP018	6.4	12.7
UP024 to UP030	9.5	15.9

