

Toshiba Air Conditioning Data Sheet

MMU-UP0301HP-E
VRF 4 WAY CASSETTE



Model Reference		MMU-UP0301HP-E	
Capacity Code		HP	3.2
Nominal	Cooling Capacity	kW	9.0
	Heating Capacity	kW	10.0
UK	Cooling Total/Sensible	kW	8.2/5.9
	Heating	kW	6.8
Electrical	Power Input	kW	0.043
	Run Current	Amps	0.43
	Start Current	Amps	0.59
Air Flow	High - Medium - Low	l/s	367 - 305 - 237
	High - Medium - Low	m ³ /h	1320 - 1100 - 850
Sound	Pressure High - Medium - Low	dB(A)	38 - 33 - 30
	Power High - Medium - Low	dB(A)	53 - 48 - 45
Unit	Height x Width x Depth	mm	256 x 840 x 840
	Weight	kg	20
Panel	Height x Width x Depth	mm	30 x 950 x 950
	Weight RBC-U41PG(W)-E	kg	4
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	32/25
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

TOSHIBA

- Two louver shape option
- Possible to set three different and swing modes
- Wide air flow in all directions
- Optimal air diffusion up to 4.6m ceiling height!
- Self-cleaning function and Ag-ion tip for anti-mould in drain cap
- Built-in high-lift drain pump
- Compact chassis with only 256mm height (up to size 30)
- Lightweight unit, for easy and quick installation

