

## Toshiba Air Conditioning Data Sheet

MMU-UP0361WH-E  
VRF 2 WAY CASSETTE



Model Reference		MMU-UP0361WH-E	
<b>Capacity Code</b>		HP	4.0
Nominal	Cooling Capacity	kW	11.2
	Heating Capacity	kW	12.5
UK	Cooling Total/Sensible	kW	10.2/7.3
	Heating	kW	8.5
Electrical	Power Input	kW	0.073
	Run Current	Amps	0.48
	Start Current	Amps	0.72
Air Flow	High - Medium - Low	l/s	483 - 398 - 328
	High - Medium - Low	m <sup>3</sup> /h	1740 - 1434 - 1182
Sound	Pressure High - Medium - Low	dB(A)	42 - 39 - 36
	Power High - Medium - Low	dB(A)	57 - 54 - 51
Unit	Height x Width x Depth	mm	345 x 1600 x 570
	Weight	kg	36
Panel	Height x Width x Depth	mm	20 x 1835 x 680
	Weight RBC-UW1403PG(W)-E	kg	14
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	32/25
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

# TOSHIBA

- Unique air flow control
- Enhanced indoor air quality with standard long-life filters
- Elegant white decoration panel
- Minimal weight (19 kg) for units up to 4.5kw
- Compact dimensions (height 295mm)
- Built-in drain pump

**UP036 to UP056**

(Unit: mm)

