

Toshiba Air Conditioning Data Sheet

MMU-UP0481HP-E
VRF 4 WAY CASSETTE



Model Reference		MMU-UP0481HP-E	
Capacity Code		HP	5.0
Nominal	Cooling Capacity	kW	14.0
	Heating Capacity	kW	16.0
UK	Cooling Total/Sensible	kW	12.7/9.3
	Heating	kW	10.9
Electrical	Power Input	kW	0.112
	Run Current	Amps	0.88
	Start Current	Amps	1.23
Air Flow	High - Medium - Low	l/s	592 - 397 - 313
	High - Medium - Low	m ³ /h	2130 - 1430 - 1130
Sound	Pressure High - Medium - Low	dB(A)	46 - 38 - 33
	Power High - Medium - Low	dB(A)	61 - 53 - 48
Unit	Height x Width x Depth	mm	319 x 840 x 840
	Weight	kg	25
Panel	Height x Width x Depth	mm	30 x 950 x 950
	Weight RBC-U41PG(W)-E	kg	4
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	32/25
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

TOSHIBA

- Two louver shape option
- Possible to set three different and swing modes
- Wide air flow in all directions
- Optimal air diffusion up to 4.6m ceiling height!
- Self-cleaning function and Ag-ion tip for anti-mould in drain cap
- Built-in high-lift drain pump
- Compact chassis with only 256mm height (up to size 30)
- Lightweight unit, for easy and quick installation

