

## Toshiba Air Conditioning Data Sheet

MMU-UP0561WH-E  
VRF 2 WAY CASSETTE



Model Reference		MMU-UP0561WH-E	
<b>Capacity Code</b>		HP	6.0
Nominal	Cooling Capacity	kW	16.0
	Heating Capacity	kW	18.0
UK	Cooling Total/Sensible	kW	14.5/9.4
	Heating	kW	12.2
Electrical	Power Input	kW	0.117
	Run Current	Amps	0.75
	Start Current	Amps	1.13
Air Flow	High - Medium - Low	l/s	567 - 438 - 367
	High - Medium - Low	m <sup>3</sup> /h	2040 - 1578 - 1320
Sound	Pressure High - Medium - Low	dB(A)	46 - 42 - 39
	Power High - Medium - Low	dB(A)	61 - 57 - 54
Unit	Height x Width x Depth	mm	345 x 1600 x 570
	Weight	kg	36
Panel	Height x Width x Depth	mm	20 x 1835 x 680
	Weight RBC-UW1403PG(W)-E	kg	14
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	32/25
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

# TOSHIBA

- Unique air flow control
- Enhanced indoor air quality with standard long-life filters
- Elegant white decoration panel
- Minimal weight (19 kg) for units up to 4.5kw
- Compact dimensions (height 295mm)
- Built-in drain pump

**UP036 to UP056**

**(Unit: mm)**

