

## Toshiba Air Conditioning Data Sheet

MMD-UP0031SPHY-E  
VRF SLIM DUCT



Model Reference		MMD-UP0031SPHY-E	
<b>Capacity Code</b>		HP	0.3
Nominal	Cooling Capacity	kW	0.9
	Heating Capacity	kW	1.0
UK	Cooling Total/Sensible	kW	0.8/0.6
	Heating	kW	0.7
Electrical	Power Input	kW	0.018
	Run Current	Amps	0.34
	Start Current	Amps	0.60
Air Flow	High - Medium - Low	l/s	114 - 103 - 97
	High - Medium - Low	m <sup>3</sup> /h	410 - 370 - 350
External Static Pressure	Standard	Pa	10
	Maximum	Pa	50
Sound pressure	Back Inlet High - Medium - Low	dB(A)	29 - 27 - 25
	Under Inlet High - Medium - Low	dB(A)	37 - 35 - 32
Sound power	Back Inlet High - Medium - Low	dB(A)	46 - 44 - 42
	Under Inlet High - Medium - Low	dB(A)	51 - 49 - 47
Unit	Height x Width x Depth	mm	210 x 700 x 450
	Weight	kg	15
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4
	Drain Pipe Connection OD/ID	mm	32/25
	Lift Pump Drain Height from Unit Base	mm	< 550
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

# TOSHIBA

- Ultra-flexible, invisible and silent
- Slimline design
- Exceptionally low noise level – down to 25 dB(A)
- Static pressure up to 50Pa.
- Built-in high lift drain pump.

■ External dimensions

