

Toshiba Air Conditioning Data Sheet

MMD-UP0071SPHY-E
VRF SLIM DUCT



Model Reference		MMD-UP0071SPHY-E	
Capacity Code		HP	0.8
Nominal	Cooling Capacity	kW	2.2
	Heating Capacity	kW	2.5
UK	Cooling Total/Sensible	kW	2.0/1.6
	Heating	kW	1.7
Electrical	Power Input	kW	0.026
	Run Current	Amps	0.40
	Start Current	Amps	0.69
Air Flow	High - Medium - Low	l/s	150 - 128 - 111
	High - Medium - Low	m ³ /h	540 - 460 - 400
External Static Pressure	Standard	Pa	10
	Maximum	Pa	50
Sound pressure	Back Inlet High - Medium - Low	dB(A)	31 - 29 - 26
	Under Inlet High - Medium - Low	dB(A)	41 - 39 - 35
Sound power	Back Inlet High - Medium - Low	dB(A)	52 - 49 - 45
	Under Inlet High - Medium - Low	dB(A)	54 - 49 - 46
Unit	Height x Width x Depth	mm	210 x 700 x 450
	Weight	kg	15
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4
	Drain Pipe Connection OD/ID	mm	32/25
	Lift Pump Drain Height from Unit Base	mm	< 550
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

TOSHIBA

- Ultra-flexible, invisible and silent
- Slimline design
- Exceptionally low noise level – down to 25 dB(A)
- Static pressure up to 50Pa.
- Built-in high lift drain pump.

■ External dimensions

