

Toshiba Air Conditioning Data Sheet

MMD-UP0091SPHY-E
VRF SLIM DUCT



Model Reference		MMD-UP0091SPHY-E	
Capacity Code		HP	1.0
Nominal	Cooling Capacity	kW	2.8
	Heating Capacity	kW	3.2
UK	Cooling Total/Sensible	kW	2.5/2.0
	Heating	kW	2.2
Electrical	Power Input	kW	0.029
	Run Current	Amps	0.42
	Start Current	Amps	0.73
Air Flow	High - Medium - Low	l/s	158 - 139 - 117
	High - Medium - Low	m ³ /h	570 - 500 - 420
External Static Pressure	Standard	Pa	10
	Maximum	Pa	50
Sound pressure	Back Inlet High - Medium - Low	dB(A)	32 - 29 - 26
	Under Inlet High - Medium - Low	dB(A)	42 - 40 - 36
Sound power	Back Inlet High - Medium - Low	dB(A)	54 - 50 - 46
	Under Inlet High - Medium - Low	dB(A)	56 - 52 - 49
Unit	Height x Width x Depth	mm	210 x 700 x 450
	Weight	kg	15
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4
	Drain Pipe Connection OD/ID	mm	32/25
	Lift Pump Drain Height from Unit Base	mm	< 550
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

TOSHIBA

- Ultra-flexible, invisible and silent
- Slimline design
- Exceptionally low noise level – down to 25 dB(A)
- Static pressure up to 50Pa.
- Built-in high lift drain pump.

■ External dimensions

