

## Toshiba Air Conditioning Data Sheet

MMD-UP0121SPHY-E  
VRF SLIM DUCT



Model Reference		MMD-UP0121SPHY-E	
<b>Capacity Code</b>		HP	1.3
Nominal	Cooling Capacity	kW	3.6
	Heating Capacity	kW	4.0
UK	Cooling Total/Sensible	kW	3.3/2.5
	Heating	kW	2.7
Electrical	Power Input	kW	0.031
	Run Current	Amps	0.44
	Start Current	Amps	0.77
Air Flow	High - Medium - Low	l/s	167 - 144 - 122
	High - Medium - Low	m <sup>3</sup> /h	600 - 520 - 440
External Static Pressure	Standard	Pa	10
	Maximum	Pa	50
Sound pressure	Back Inlet High - Medium - Low	dB(A)	33 - 30 - 27
	Under Inlet High - Medium - Low	dB(A)	44 - 40 - 37
Sound power	Back Inlet High - Medium - Low	dB(A)	54 - 50 - 46
	Under Inlet High - Medium - Low	dB(A)	57 - 53 - 49
Unit	Height x Width x Depth	mm	210 x 700 x 450
	Weight	kg	15
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4
	Drain Pipe Connection OD/ID	mm	32/25
	Lift Pump Drain Height from Unit Base	mm	< 550
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

# TOSHIBA

- Ultra-flexible, invisible and silent
- Slimline design
- Exceptionally low noise level – down to 25 dB(A)
- Static pressure up to 50Pa.
- Built-in high lift drain pump.

## ■ External dimensions

