

Toshiba Air Conditioning Data Sheet

MMD-UP0151SPHY-E
VRF SLIM DUCT



Model Reference		MMD-UP0151SPHY-E	
Capacity Code		HP	1.7
Nominal	Cooling Capacity	kW	4.5
	Heating Capacity	kW	5.0
UK	Cooling Total/Sensible	kW	4.1/2.9
	Heating	kW	3.4
Electrical	Power Input	kW	0.035
	Run Current	Amps	0.47
	Start Current	Amps	0.82
Air Flow	High - Medium - Low	l/s	192 - 178 - 153
	High - Medium - Low	m ³ /h	690 - 640 - 550
External Static Pressure	Standard	Pa	10
	Maximum	Pa	50
Sound pressure	Back Inlet High - Medium - Low	dB(A)	33 - 30 - 28
	Under Inlet High - Medium - Low	dB(A)	42 - 39 - 37
Sound power	Back Inlet High - Medium - Low	dB(A)	52 - 50 - 46
	Under Inlet High - Medium - Low	dB(A)	55 - 53 - 49
Unit	Height x Width x Depth	mm	210 x 900 x 450
	Weight	kg	19
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	32/25
	Lift Pump Drain Height from Unit Base	mm	< 650
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

TOSHIBA

- Ultra-flexible, invisible and silent
- Slimline design
- Exceptionally low noise level – down to 25 dB(A)
- Static pressure up to 50Pa.
- Built-in high lift drain pump.

■ External dimensions

