

Toshiba Air Conditioning Data Sheet

MMD-UP0181SPHY-E
VRF SLIM DUCT



Model Reference		MMD-UP0181SPHY-E	
Capacity Code		HP	2.0
Nominal	Cooling Capacity	kW	5.6
	Heating Capacity	kW	6.3
UK	Cooling Total/Sensible	kW	5.1/3.5
	Heating	kW	4.3
Electrical	Power Input	kW	0.044
	Run Current	Amps	0.53
	Start Current	Amps	0.92
Air Flow	High - Medium - Low	l/s	217 - 203 - 181
	High - Medium - Low	m ³ /h	780 - 730 - 650
External Static Pressure	Standard	Pa	10
	Maximum	Pa	50
Sound pressure	Back Inlet High - Medium - Low	dB(A)	34 - 32 - 29
	Under Inlet High - Medium - Low	dB(A)	44 - 42 - 39
Sound power	Back Inlet High - Medium - Low	dB(A)	56 - 54 - 51
	Under Inlet High - Medium - Low	dB(A)	57 - 55 - 52
Unit	Height x Width x Depth	mm	210 x 900 x 450
	Weight	kg	19
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	32/25
	Lift Pump Drain Height from Unit Base	mm	< 650
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

TOSHIBA

- Ultra-flexible, invisible and silent
- Slimline design
- Exceptionally low noise level – down to 25 dB(A)
- Static pressure up to 50Pa.
- Built-in high lift drain pump.

■ External dimensions

