

Toshiba Air Conditioning Data Sheet

MMD-UP0241SPHY-E
VRF SLIM DUCT



Model Reference		MMD-UP0241SPHY-E	
Capacity Code		HP	2.5
Nominal	Cooling Capacity	kW	7.1
	Heating Capacity	kW	8.0
UK	Cooling Total/Sensible	kW	6.4/4.4
	Heating	kW	5.4
Electrical	Power Input	kW	0.067
	Run Current	Amps	0.59
	Start Current	Amps	1.21
Air Flow	High - Medium - Low	l/s	300 - 264 - 239
	High - Medium - Low	m ³ /h	1080 - 950 - 860
External Static Pressure	Standard	Pa	10
	Maximum	Pa	50
Sound pressure	Back Inlet High - Medium - Low	dB(A)	36 - 33 - 30
	Under Inlet High - Medium - Low	dB(A)	47 - 44 - 41
Sound power	Back Inlet High - Medium - Low	dB(A)	60 - 56 - 53
	Under Inlet High - Medium - Low	dB(A)	64 - 60 - 58
Unit	Height x Width x Depth	mm	210 x 1100 x 450
	Weight	kg	22
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	32/25
	Lift Pump Drain Height from Unit Base	mm	<750
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

TOSHIBA

- Ultra-flexible, invisible and silent
- Slimline design
- Exceptionally low noise level – down to 25 dB(A)
- Static pressure up to 50Pa.
- Built-in high lift drain pump.

■ External dimensions

