

Toshiba Air Conditioning Data Sheet

MMD-UP0271SPHY-E
VRF SLIM DUCT



Model Reference		MMD-UP0271SPHY-E	
Capacity Code		HP	3.0
Nominal	Cooling Capacity	kW	8.0
	Heating Capacity	kW	9.0
UK	Cooling Total/Sensible	kW	7.3/4.9
	Heating	kW	6.1
Electrical	Power Input	kW	0.072
	Run Current	Amps	0.74
	Start Current	Amps	1.30
Air Flow	High - Medium - Low	l/s	317 - 272 - 253
	High - Medium - Low	m ³ /h	1140 - 980 - 910
External Static Pressure	Standard	Pa	10
	Maximum	Pa	50
Sound pressure	Back Inlet High - Medium - Low	dB(A)	37 - 34 - 32
	Under Inlet High - Medium - Low	dB(A)	48 - 45 - 43
Sound power	Back Inlet High - Medium - Low	dB(A)	61 - 58 - 55
	Under Inlet High - Medium - Low	dB(A)	65 - 61 - 59
Unit	Height x Width x Depth	mm	210 x 1100 x 450
	Weight	kg	22
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	32/25
	Lift Pump Drain Height from Unit Base	mm	< 750
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

TOSHIBA

- Ultra-flexible, invisible and silent
- Slimline design
- Exceptionally low noise level – down to 25 dB(A)
- Static pressure up to 50Pa.
- Built-in high lift drain pump.

■ External dimensions

