

## Toshiba Air Conditioning Data Sheet

MMD-UP0721HP-E  
VRF HIGH STATIC DUCTED



Model Reference		MMD-UP0721HP-E	
<b>Capacity Code</b>		HP	8.0
Nominal	Cooling Capacity	kW	22.4
	Heating Capacity	kW	25.0
UK	Cooling Total/Sensible	kW	20.3/14.1
	Heating	kW	17.0
Electrical	Power Input	kW	0.540
	Run Current	Amps	2.83
	Start Current	Amps	7.80
Air Flow	High - Medium - Low	l/s	1056 - 889 - 694
	High - Medium - Low	m <sup>3</sup> /h	3800 - 3200 - 2500
External Static Pressure	Standard	Pa	150
	Maximum	Pa	250
Sound	Pressure High - Medium - Low	dB(A)	44 - 40 - 36
	Power High - Medium - Low	dB(A)	59 - 55 - 51
Unit	Height x Width x Depth	mm	448 x 1400 x 900
	Weight	kg	97
Pipe Connection	Flare Connections (gas - liquid)	inch	7/8 - 1/2
	Drain Pipe Connection OD/ID	mm	32/25
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-16

# TOSHIBA

- Ultra-flexible, invisible and silent unit
- Diffuser design flexibility
- Unobtrusive, flexible and compact
- Static pressure can be set to 7 levels from 50 to 250Pa
- Long-life filter and air discharge spigot available
- Built-in high-lift drain pump (sizes 18 to 56)

## External dimensions

(Unit: mm)

