


Toshiba Air Conditioning Data Sheet

MMK-UP0301HP-E
VRF HIGH WALL



Model Reference		MMK-UP0301HP-E	
Capacity Code		HP	3.2
Nominal	Cooling Capacity	kW	9.0
	Heating Capacity	kW	10.0
UK	Cooling Total/Sensible	kW	-/*
	Heating	kW	6.8
Electrical	Power Input	kW	0.054
	Run Current	Amps	0.05
	Start Current	Amps	0.50
Air Flow	High - Medium - Low	l/s	403 - 361 - 305
	High - Medium - Low	m ³ /h	1450 - 1300 - 1100
Sound	Pressure High - Medium - Low	dB(A)	48 - 44 - 41
	Power High - Medium - Low	dB(A)	63 - 59 - 56
Unit	Height x Width x Depth	mm	350 x 1200 x 280
	Weight	kg	20
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	16/14
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5
Remote Controller			WH-TA09NE (Infra-Red)

*/- Awaiting published data

TOSHIBA

- The unit is compact and lightweight, it is perfect for installation above the doors or in narrow corridors.
- New appearance, simple, elegant with nice led display.
- Special fin coating for Healthy & Fresh air.
- Ultra pure filter (818F0050) available as an option to ensure healthy and pleasant atmosphere.
- Remote controller for easy access to the preferred setting.
- Filters for dust collection can be easily removed by lifting the front panel and can be cleaned easily washing them under running water.

MMK-UP0151HP(L)* / MMK-UP0181HP(L)* / MMK-UP0241HP(L)*

