

Toshiba Air Conditioning Data Sheet

MML-UP0071H-E
VRF FLOOR MOUNTED CONSOLE



Model Reference		MML-UP0071H-E	
Capacity Code		HP	0.8
Nominal	Cooling Capacity	kW	2.2
	Heating Capacity	kW	2.5
UK	Cooling Total/Sensible	kW	2.0/1.3
	Heating	kW	1.7
Electrical	Power Input	kW	0.056
	Run Current	Amps	0.26
	Start Current	Amps	0.60
Air Flow	High - Medium - Low	l/s	133 - 117 - 100
	High - Medium - Low	m ³ /h	480 - 420 - 360
Sound	Pressure High - Medium - Low	dB(A)	39 - 37 - 35
	Power High - Medium - Low	dB(A)	54 - 52 - 50
Unit	Height x Width x Depth	mm	630 x 950 x 230
	Weight	kg	37
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4
	Drain Pipe Connection OD/ID	mm	26/20
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

TOSHIBA

- Air flow adaptability and flexibility
- One single cabinet size for all capacity models,
- Minimum space required for installation and servicing
- Refrigerant and drain piping with four installation possibilities: top, rear, left or right hand of the unit.

External dimensions

(Unit: mm)

