

Toshiba Air Conditioning Data Sheet

MML-UP0091H-E
VRF FLOOR MOUNTED CONSOLE



| Model Reference | | MML-UP0091H-E | |
|----------------------|----------------------------------|-------------------|-----------------|
| Capacity Code | | HP | 1.0 |
| Nominal | Cooling Capacity | kW | 2.8 |
| | Heating Capacity | kW | 3.2 |
| UK | Cooling Total/Sensible | kW | 2.5/1.5 |
| | Heating | kW | 2.2 |
| Electrical | Power Input | kW | 0.056 |
| | Run Current | Amps | 0.26 |
| | Start Current | Amps | 0.60 |
| Air Flow | High - Medium - Low | l/s | 133 - 117 - 100 |
| | High - Medium - Low | m ³ /h | 480 - 420 - 360 |
| Sound | Pressure High - Medium - Low | dB(A) | 39 - 37 - 35 |
| | Power High - Medium - Low | dB(A) | 54 - 52 - 50 |
| Unit | Height x Width x Depth | mm | 630 x 950 x 230 |
| | Weight | kg | 37 |
| Pipe Connection | Flare Connections (gas - liquid) | inch | 3/8 - 1/4 |
| | Drain Pipe Connection OD/ID | mm | 26/20 |
| Power Supply | Suggested Fuse Size | V/ph/Hz-A | 220-240/1/50-5 |

TOSHIBA

- Air flow adaptability and flexibility
- One single cabinet size for all capacity models,
- Minimum space required for installation and servicing
- Refrigerant and drain piping with four installation possibilities: top, rear, left or right hand of the unit.

External dimensions

(Unit: mm)

