

Toshiba Air Conditioning Data Sheet

MML-UP0121H-E
VRF FLOOR MOUNTED CONSOLE



Model Reference		MML-UP0121H-E	
Capacity Code		HP	1.3
Nominal	Cooling Capacity	kW	3.6
	Heating Capacity	kW	4.0
UK	Cooling Total/Sensible	kW	3.3/2.1
	Heating	kW	2.7
Electrical	Power Input	kW	0.092
	Run Current	Amps	0.43
	Start Current	Amps	0.80
Air Flow	High - Medium - Low	l/s	250 - 217 - 180
	High - Medium - Low	m ³ /h	900 - 780 - 650
Sound	Pressure High - Medium - Low	dB(A)	45 - 41 - 38
	Power High - Medium - Low	dB(A)	60 - 56 - 53
Unit	Height x Width x Depth	mm	630 x 950 x 230
	Weight	kg	37
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4
	Drain Pipe Connection OD/ID	mm	26/20
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

TOSHIBA

- Air flow adaptability and flexibility
- One single cabinet size for all capacity models,
- Minimum space required for installation and servicing
- Refrigerant and drain piping with four installation possibilities: top, rear, left or right hand of the unit.

External dimensions

(Unit: mm)

