

## Toshiba Air Conditioning Data Sheet

MML-UP0241H-E  
VRF FLOOR MOUNTED CONSOLE



Model Reference	MML-UP0241H-E		
<b>Capacity Code</b>		HP	2.5
Nominal	Cooling Capacity	kW	7.1
	Heating Capacity	kW	8.0
UK	Cooling Total/Sensible	kW	6.4/4.2
	Heating	kW	5.4
Electrical	Power Input	kW	0.102
	Run Current	Amps	0.47
	Start Current	Amps	1.10
Air Flow	High - Medium - Low	l/s	300 - 267 - 217
	High - Medium - Low	m <sup>3</sup> /h	1080 - 930 - 780
Sound	Pressure High - Medium - Low	dB(A)	49 - 44 - 39
	Power High - Medium - Low	dB(A)	64 - 59 - 54
Unit	Height x Width x Depth	mm	630 x 950 x 230
	Weight	kg	40
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	26/20
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

# TOSHIBA

- Air flow adaptability and flexibility
- One single cabinet size for all capacity models,
- Minimum space required for installation and servicing
- Refrigerant and drain piping with four installation possibilities: top, rear, left or right hand of the unit.

## External dimensions

(Unit: mm)

