

## Toshiba Air Conditioning Data Sheet

MMD-UP0961HFP-E  
VRF FRESH AIR INTAKE



Model Reference		MMD-UP0961HFP-E	
<b>Capacity Code</b>		HP	10.0
Nominal	Cooling Capacity	kW	28.0
	Heating Capacity	kW	17.4
UK	Cooling Total	kW	15.3
	Heating	kW	21.0
Operating Limits	Indoor Temperature Range C/H	°C	13-25/18-30
	Cooling Limit	°C	+22
	Ambient Cooling Fan Only	°C	≥ +5/≤ +22
	Heating Limit	°C	≥ -10/≤ +15
	Fan Stop Cooling - Heating	°C	≤ +5/≤ -10
Electrical	Power Input	kW	0.200
	Run Current	Amps	1.07
	Start Current	Amps	583
Air Flow	Standard	l/s	700 - 367
	Upper - Lower	l/s	2100
	Standard	m <sup>3</sup> /h	2520 - 1320
	Upper - Lower	m <sup>3</sup> /h	100
External Static Pressure	Standard	Pa	200 - 50
	Upper - Lower	Pa	39 - 36 - 33
Sound	Pressure High - Medium - Low	dB(A)	54 - 51 - 48
	Power High - Medium - Low	dB(A)	477x 1430x 900
Unit	Height x Width x Depth	mm	99
	Weight	kg	7/8 - 1/2
Pipe Connection	Flare Connections (gas - liquid)	inch	32/25
	Drain Pipe Connection OD/ID	mm	±0.5
Height Difference	Fresh Air Intake To Fresh Air Intake	m	±40
	Fresh Air Intake To Indoor	m	220-240/1/50-15
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-15

# TOSHIBA

- Capacity – 8.9 > 40 kW (5 to 14HP)
- Sound Level – Max 42 dB
- Air Flow – 1080 > 3060 m<sup>3</sup>/h
- Pre-heat, pre-cool functions
- Adaptability: External static pressure available up to 200 Pa
- Standard and high-performance filters available as an option.
- TU2C-Link control connection.

## MMD-UP0721HFP-E to MMD-UP1281HFP-E

