

Toshiba Air Conditioning Data Sheet

MMF-UP0181H-E
VRF FLOOR MOUNTED CABINET



Model Reference		MMF-UP0181H-E	
Capacity Code		HP	2.0
Nominal	Cooling Capacity	kW	5.6
	Heating Capacity	kW	6.3
UK	Cooling Total/Sensible	kW	5.1/3.9
	Heating	kW	4.3
Electrical	Power Input	kW	0.055
	Run Current	Amps	0.38
	Start Current	Amps	0.53
Air Flow	High - Medium - Low	l/s	250 - 217 - 183
	High - Medium - Low	m ³ /h	900 - 780 - 660
Sound	Pressure High - Medium - Low	dB(A)	46 - 42 - 37
	Power High - Medium - Low	dB(A)	61 - 57 - 52
Unit	Height x Width x Depth	mm	1750 x 600 x 210
	Weight	kg	46
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	20 male screw
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

TOSHIBA

- High air flows: From 180 l/s to 600 l/s (660 m³/h to 2160 m³/h)
- Wide air distribution angle: up to 150°
- Cooling capacities from 4.5 kW to 16 kW
- Heating capacities from 5 kW to 18 kW
- Very small footprint: 0.128 m² up to 8 kW and 0.243 m² up to 16 kW

External views

(Unit: mm)

