

## Toshiba Air Conditioning Data Sheet

MMF-UP0481H-E  
VRF FLOOR MOUNTED CABINET



Model Reference		MMF-UP0481H-E	
<b>Capacity Code</b>		HP	5.0
Nominal	Cooling Capacity	kW	14.0
	Heating Capacity	kW	16.0
UK	Cooling Total/Sensible	kW	12.7/9.3
	Heating	kW	10.9
Electrical	Power Input	kW	0.160
	Run Current	Amps	1.10
	Start Current	Amps	1.54
Air Flow	High - Medium - Low	l/s	600 - 481 - 433
	High - Medium - Low	m <sup>3</sup> /h	2160 - 1730 - 1560
Sound	Pressure High - Medium - Low	dB(A)	54 - 49 - 44
	Power High - Medium - Low	dB(A)	69 - 64 - 59
Unit	Height x Width x Depth	mm	1750 x 600 x 390
	Weight	kg	62
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	20 male screw
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

# TOSHIBA

- High air flows: From 180 l/s to 600 l/s (660 m<sup>3</sup>/h to 2160 m<sup>3</sup>/h)
- Wide air distribution angle: up to 150°
- Cooling capacities from 4.5 kW to 16 kW
- Heating capacities from 5 kW to 18 kW
- Very small footprint: 0.128 m<sup>2</sup> up to 8 kW and 0.243 m<sup>2</sup> up to 16 kW

## External views

(Unit: mm)

