

Toshiba Air Conditioning Data Sheet

RAS-13E2AVG-E
SEIYA (E2) OUTDOOR UNIT



Model Reference		RAS-13E2AVG-E	
Nominal	Cooling Capacity	kW	3.3
	Heating Capacity	kW	3.6
	EER/COP	W/W	3.00/3.91
UK	Cooling Total/Sensible	kW	3.22/2.49
	Heating	kW	2.20
Cooling EN14825	Range Min. - Max.	kW	1.20 - 3.60
	Power Input	kW	1.10
	Pdesign	kW	3.3
	SEER/Energy Efficiency Class		7.00/A++
	Seasonal Energy Consumption	kWh/a	165
Heating EN14825	Range Min. - Max.	kW	0.97 - 4.50
	Power Input	kW	0.92
	Pdesign	kW	2.7
	SCOP/Energy Efficiency Class		4.60/A++
	Seasonal Energy Consumption	kWh/a	822
Operating range	Cooling/Heating	°C	-15 ~ 46/-15 ~ 24
Air Flow	High	m ³ /h - l/s	1980 - 550
Sound	Pressure High Cooling/Heating/Silent	dB(A)	48 - 49 - 43
	Power High Cooling/Heating/Silent	dB(A)	61 - 62 - 56
Unit	Height x Width x Depth	mm	530 x 660 x 240
	Weight	kg	22
Pipe Connection	Flare Connections (gas-liquid)	inch	3/8" - 1/4"
	Min.-Max. Length	m	2-15
	Maximum Height Difference	m	±12
	Drain Port Connection	mm	16
Refrigerant R32	Base Charge/Chargeless Length	m	0.54/15
	Additional Charge	g/m	0
Run Current	Maximum	Amps	-/*
Power Cable	Outdoor to Indoor		3 core + earth
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-10

TOSHIBA

- invisible piping cut-out
- ultra fresh filter
- new remote control
- wireless adapter is supported and can be installed inside the indoor unit
- supports energy monitoring; remote control is connectable with wires and dustless heat exchanger

(Unit : mm)

